

Holik Gloves Raven and Fury NFPA 1970 Models User guide / Instructions for Use

August, 2025 Rev. 1

These structural firefighting gloves should be used as part of a complete protective ensemble for use during structural firefighting. Consult with your department management regarding appropriate use.

These gloves cannot provide complete protection under all conditions and circumstances and against all hazards that may be encountered during structural firefighting.

Gloves should be marked on the inside only using a fine marker.

Most of the performance properties of these gloves that have qualified them for compliance to NFPA 1970:2025 cannot be tested in the field.

Warning! The moisture barrier has not been evaluated for all chemicals that can be encountered during firefighting operations. The effects of chemical exposure on the moisture barrier are to be evaluated per the inspection procedures in NFPA 1851.

Holik International s.r.o. warrants that all protective fire gloves are free from defects in material and workmanship for the useful life of the product, not more than 2 years. This warranty specifically excludes accidental damage (acid, tears on nails, etc.), natural disasters, intentional or unintentional abuse, damage caused by disregard of care instructions, and normal wear.

Gloves should fit comfortable and secure but not too tight.

Store gloves only in a dry condition and out of direct sunlight. Do not store wet gloves.

Inspect gloves prior to each use. Gloves with holes, torn seams or any other condition that may be expected to compromise protection should be retired.

Donning and doffing procedures:

Don gloves by inserting the fingers and pulling from the cuff edge in the most convenient area. For wet gloves alternate pulling from various areas of the cuff edge if necessary. Doff gloves by pulling from the middle three fingers.

Sizing and adjustment procedures:

If there is notable difficulty with donning then consider moving up one size.

For gloves used with turnout gear sleeves having knit wristlets, gauntlet style gloves should be used. For gloves used with turnout gear sleeves having no knit wristlets, knit wristlet style gloves should be used.

Proper use consistent with NFPA 1500, Standard on Fire Department Occupational Safety and Health Program, and 29 CFR 1910.132, General Requirements of Subpart I, "Personal Protective Equipment" The use of these gloves should be consistent with NFPA 1500, Standard on Fire Department Occupational Safety and Health Program, and 29 CFR 1910.132, General Requirements of Subpart I, "Personal Protective Equipment".

Storage: Store the gloves in dark and dry conditions in temperature between 50-77°F (10–25°C).

Maintenance: Remove excess dirt after every use. Rinse the gloves in warm water. A gentle detergent can be used, but do not bleach. After washing put your hand into the glove to shape it. Allow to dry naturally, do not tumble dry or use any artificial heat source.

Checking and usage of gloves:

After each use give the gloves a visual inspection, paying particular attention to the seams. If you find damage to the gloves to the extent that it cannot ensure hand protection, do not use them. No glove can provide hundred-per-cent protection. **! Use caution in all activities!**

Visually inspect all areas of gloves including inside liner as much as possible prior to each use.

Do not attempt repair of gloves. In case of damaged gloves retire them or contact manufacturer.

In case of chemical or biological contamination gloves should be disposed of according to the relevant state and/or local regulations.

Gloves worn out to the point where protective properties are believed to be compromised should be disposed. Non-contaminated gloves can be disposed of with regular waste according to local and/or state regulations.